



**SDJ MANUAL STACKER TRUCK SPECIFICATION**

1	Model		SDJ1016/SDJAS10	SDJ1025/SDJAS10	SDJ1030/SDJAS1	SDJ1516/SDJAS151	SDJ1525/SDJAS1	SDJ1530/SDJAS1530	SDJ2016/SDJAS20
			16	25	030	6	525		16
2	Load capacity	kg	1000	1000	1000	1500	1500	1500	2000
3	Load center	c(mm)	500	500	500	400	400	400	400
4	Service weight	kg	250	290	316	270	310	336	290
5	Lowered mast height	h1(mm)	2080	1830	2080	2080	1830	2080	2080
6	Lifting height	h3(mm)	1600	2500	3000	1600	2500	3000	1600
7	Overall height	h4(mm)	2080	3000	3500	2080	3000	3500	2080
8	Fork lowered height	h13(mm)	90	90	90	90	90	90	90
9	Overall length	l1(mm)	1280	1280	1280	1280	1280	1280	1280
10	Overall width	b1(mm)	700/980	700/980	700/980	700/980	700/980	700/980	700/980
11	Fork dimensions	s/e/l(mm)	Forge fork:35×100×900, fixed type 60×142×1100, mobile type60×142×900						
12	Width overall forks	b5(mm)	550/660	550/660	550/660	550/660	550/660	550/660	550/660
13	Ground clearance	m1(mm)	25	25	25	25	25	25	25
14	Turning radius	mm	1200	1200	1200	1200	1200	1200	1200
15	Lifting speed laden/unladen	mm/stroke	9.5/10.5	9.5/10.5	9.5/10.5	9.5/10.5	9.5/10.5	9.5/10.5	9.5/10.5
16	Lowering speed laden/unladen	mm/s	Manual control						