

carry·UP **FB20~FB25 4-WHEEL FORKLIFT SPECIFICATION**

Specification	1	Model			FB20	FB25
	2	Power type			electric	electric
	3	Rated Capacity		kg	2000	2500
	4	Load Centre		mm	500	500
	5	Lifting Height		mm	3000	3000
	6	Fork Size	L×W×T	mm	1070×120×40	1070×120×40
	7	Tilting Angle	F/R (α°/β°)	Deg	6/12	6/12
Dimensions	8	Overall Dimension	Length (to fork face)	mm	2360	2360
	9		Overall Width	mm	1160	1160
	10		Mast Lowered Height	mm	2070	2070
	11		Mast Extended Height (with backrest)	mm	4020	4020
	12		Overhead Guard Height	mm	2240	2240
	13	Turning Radius	outside	mm	2075	2075
	14	Turning Radius	Min. insecting aisle	mm	2250	2250
	15	Front Overhang		mm	465	465
	16	Tread	(Front/Rear)	mm	960/950	960/950
	17	Ground Clearance	Min.	mm	110	110
	18	Wheelbase		mm	1510	1510
	Performance	19	Fork Spread	Min./Max.	mm	240/1020
20		Speed	Travel (Laden)	km/h	15	15
21			Lifting (Laden)	mm/s	300	270
22		Max.Gradeability	Laden	%	15	15
23		Service Weight (include battery)		kg	4170	4410
24		Tire	Front		7.00-12-12PR	7.00-12-12PR
25	Rear			18×7-8-14PR	18×7-8-14PR	
Driven	26	Motor	Driven Motor	kw	11	11
	27		Lift Motor	kw	8.6	8.6
	28	Battery	Standard	V/Ah	48/560	48/630
	29	Controller	Manufacturer		CURTIS AC	CURTIS AC
	30	Operating Pressure for Attachment		Mpa	17.5	17.5

