

General	1	Model		CBD20Q		
	2	Power Type		Electric		
	3	Operation Type		Stand-on		
	4	Rated Capacity	kg	2000		
	5	Load Centre	c(mm)	600		
Characteristic&Dimension	6	Tyre	Front /rear type	mm	PU/PU	
	7		Front wheel size	mm	φ215×75	
	8		Driving wheel size	mm	φ80×70	
	9		Balance wheel size	mm	φ100×40	
	10		front/rear number (X=drive)	mm	1X+2 / 4	
	11	Overall Dimension	Backrest height	h1(mm)	1406	
	12		Lifting height	h2(mm)	120	
	13		Min. Height	h3(mm)	85	
	14		Wheelbase	y(mm)	2117	
	15		Overall Length	l1(mm)	2461	
	16		Overall width(without forks)	l2(mm)	1311	
	17		Overall width	b1(mm)	730	
	18		Fork Dimensions	l/e/s(mm)	1150×175×75	
	19		Forks spread	b5(mm)	540	
20	Turning Radius		Wa(mm)	2300		
21	Aisle Width for pallet 1000*1200		Ast(mm)	3045		
Performance	22	Speed	Travel (laden/unladen)	km/h	4.6/5.6	
	23		Lifting (laden/unladen)	mm/s	26/34	
	24		Lowering (laden/unladen)	mm/s	/	
	25	Steering type			Manul	
	26	Service brake type			Electromagnetism	
	27	Service brake			Handle	
	28	Parking brake type			Electromagnetism	
	29	Max.Gradeability(Laden/unladen)		%	6/10	
	30	Service weight(include battery)		kg	900	
Power&Transmission	31	Motor	Drive motor type		AC/DC	
	32		Drive motor	kw	1.5/1.2	
	33		Lift motor type		DC	
	34		Lift motor	kw	2.2	
	35	Battery	Voltage/Capacity		V/Ah	24/210
	36		Weight		kg	200

