



## CDDR10/CTDR10 ELECTRIC STACKER SPECIFICATION

Specification	1	Model		CDDR10	CTDR10	
	2	Operating Type		Walkie	Walkie	
	3	Leg Type		Narrow Leg	Straddle Leg	
	4	Power Type		Electric	Electric	
	5	Load Centre	mm	600	600	
	6	Wheels Type	mm	PU	PU	
	7	Wheel Base	mm	1150	1204	
	8	Wheel Quantity	mm	1D / 1B / 4F	1D / 1B / 2F	
Dimensions	9	Standard Lift Height		mm	2000/2500/3000/3300	2000/2500/3000/3300
	10	Lowered Fork Height		mm	90	55
	16	Max Extend Height		mm	2385/2885/3385/3685	2387/2887/3387/3687
	17	Mast Lowered Height		mm	1550/1800/2050/2200	1615/1865/2115/2265
	11	Fork Size(length/width/thickness)		mm	1150(1220)/185/55	1070/100/40
	12	Overall Length		mm	1733	1721
	13	Overall Width		mm	790	940
	14	Outside Width Between Forks		mm	550/600/650/685	200—812
	15	Inside Width between Forks		mm	180/230/280/315	0—612
	18	Min.Turning Radius		mm	1350	1411
	19	Min.Aisle Width for Pallets 800×1200		mm	1914	1970
	20	Min.Aisle Width for Pallets 1000×1200		mm	1955	2010
	21	Min.ground Clearance		mm	30	50
Performance	22	Speed	Travel (Laden/unladen)	km/h	3/3.5	3/3.5
	23		Lifting (Laden/unladen)	mm/s	130/230	130/230
	24		Lowering (Laden/unladen)	mm/s	130/230	130/230
	25	Max.Gradeability	(Laden/unladen)	%	5/7	5/7
	26	Service Weight (include battery )		kg	580	596
Driven	27	Motor	Driven Motor	kw	DC 0.63	DC 0.63
	28		Lift Motor	kw	DC 2.0	DC 2.0
	29		Steering Motor	kw	/	/
	30	Battery	Standard	V/Ah	24/70	24/70
	31	Controller	Manufacturer		CURTIS	CURTIS
	32	Brake			Electromagnetic / Regenerative	Electromagnetic / Regenerative