



CDD10R-E/CDD12R-E/CDD15R-E ELECTRIC STACKER

Specification	1	Model		CDD10R-E/CDD12R-E/CDD15R-E
	2	Operating Type		Walkie
	3	Power Type		Electric
	4	Load Capacity	kg	1000/1200/1500
	5	Load Center	c(mm)	500
	6	Wheel Type		Polyurethane
Dimensions	7	Lowered Mast Height		h1(mm) 2080/1830/2080/2230/2330
	8	Max.lifting Height		h3(mm) 1600/2500/3000/3300/3500
	9	Overall Height		h4(mm) 2050/2950/3450/3600/3950
	10	Lowered Fork Height		h13(mm) 90
	11	Overall Length		l1(mm) 1750
	12	Overall Width		b1(mm) 790
	13	Fork Dimensions		S/e/l(mm) 60/160/1070
	14	Width over Forks		b5(mm) 570/685
	15	Aisle Width, with Pallet 1000x1200 Crosswise		Ast(mm) 2420
	16	Aisle Width, with Pallet 800x1200 Lengthwise		Ast(mm) 2350
	17	Groud Clearance		m2(mm) 58
	18	Turning Radius		mm 1390
Performance	19	Speed	Travel (Laden/unladen)	km/h 3.5/4
	20		Lifting (Laden/unladen)	m/s 0.1/0.2
	21		Lowering(Laden/unladen)	m/s 0.12/0-0.1
	22	Max.Gradeability	(Laden/unladen)	% 3/10
	23	Service Weight (include battery)		kg 553
Driven	24	Service Brake		Electromagnetic / Regenerative
	25	Motor	Driven Motor	kw 0.75
	26		Lift Motor	kw 2
	27		Steering Motor	/
	28	Battery	Voltage/noinal Capacity	V/Ah 24V/75AH / 24V/120AH
	29	Noise Level Operator's Ear,according to DIN12053		db(A) <70